

Excavators (Medium)

320-340



Buckets

	Model	Width Range		Capacity Range	
		mm	(in)	m ³	(yd ³)
General Duty	320-340	600-1650	(24-65)	0.46-2.12	(0.61-2.77)
Heavy Duty	320-340	1200-1350	(48-74)	1.19-2.81	(1.56-3.67)
Severe Duty	320-340	1200-1350	(48-66)	1.20-2.81	(1.57-3.67)
Ditch Cleaning	320-340	2000-2400	(78-95)	1.18-2.00	(1.54-2.61)
Ditch Cleaning Tilttable	320-340	2000-2400	(78-95)	1.15-1.43	(1.50-1.87)
Skeleton	320-340	1260-1520	(49-60)	1.09-2.01	(1.42-2.62)
Profile	300, 400 and 500 mm bottom width, wing angle from 26.5 to 45 degrees adjustable				



Couplers

	Model	Hook	Wide mm	Hydraulic Mechanical
Quick Coupler	CW-40-D.4.N	in Center	550	Mechanical
Quick Coupler	CW-40-D.4.N	Not in Center	550	Mechanical
Quick Coupler	CW-40-H.4.N	in Center	550	Hydraulic
Quick Coupler	CW-40-H.4.N	Not in Center	550	Hydraulic
Quick Coupler	CW-40s-D.4.N	in Center	420	Mechanical
Quick Coupler	CW-40s-D.4.N	Not in Center	420	Mechanical
Quick Coupler	CW-40s-H.4.N	in Center	420	Hydraulic
Quick Coupler	CW-40-H.4.N	Not in Center	420	Hydraulic
Quick Coupler	CW-45-D.4.N	in Center	490	Mechanical
Quick Coupler	CW-45-D.4.N	Not in Center	490	Mechanical
Quick Coupler	CW-45-H.4.N	in Center	490	Hydraulic
Quick Coupler	CW-45-H.4.N	Not in Center	490	Hydraulic
Quick Coupler	CW-45s-D.4.N	in Center	550	Mechanical
Quick Coupler	CW-45s-D.4.N	Not in Center	550	Mechanical
Quick Coupler	CW-45s-H.4.N	in Center	550	Hydraulic
Quick Coupler	CW-45s-H.4.N	Not in Center	550	Hydraulic



CAG Interface between CW and free hanging grabs

	Fits to CW-	Bush size
CAG-40 65x200	CW-40	65x200
CAG-40S 65x200	CW-40S	65x200
CAG-40 70x281	CW-40	70x281
CAG-40S 70x281	CW-40	70x281
CAG-40 ("B")	CW-40	B-linkage
CAG-40 ("CB")	CW-40	CB-linkage
CAG-45S ("CB")	CW-40S	CB-linkage
CAG-45 ("DB")	CW-45	DB-linkage
CAG-45S ("DB")	CW-40S	DB-linkage
CAG-45 ("TB")	CW-45	TB-linkage
CAG-45S ("TB")	CW-45S	TB-linkage
CAG-55 ("TB")	CW-55	TB-linkage
CAG-55 ("UB")	CW-55	UB-linkage
CAG-55 ("T")	CW-55	T-linkage

Auto-Connect CWAC

	Model	
Weight (approx.)	CWAC-40	340 kg
QC-pins	CWAC-40	60 mm
Width	CWAC-40	550 mm
Length	CWAC-40	475 mm
Hoisting-Hook	CWAC-40	10 t
Total Fluid connectings	CWAC-40	5
Hose couplings High flow	CWAC-40	5
Hose couplings Medium flow	CWAC-40	2 x 1"
Hose couplings Extra / Drain	CWAC-40	2 x 1/2"
Severe Duty Pin Grabber Performance	CWAC-40	1 x 1/2"



Excavators (Medium)

320-340



Matching Guide

Quick-Coupler	Linkage	Hydraulic Excavators*
CWAC-40	B	320-323

	Model	Weight kg	(lb)
Center Lock™ Pin Grabber	320-336	367-558	(809-1230)

* Please contact your Caterpillar dealer for couplers for non-current and/or special Cat machines



Grapples (GSH, GSM and G300 series)



Orange Peel Grabs

	Model	Capacity Range m ³	(yd ³)
GSH15B	320	400-800	(0.525-1.045)
GSH20B	320-329	600-1000	(0.785-1.310)
GSH22B	324-336	600-1500	(0.785-1.960)
GSM25	312-320	400-800	(0.525-1.045)
GSM35	320-329	600-1000	(0.785-1.310)
GSM45	324-336	1000-1250	(1.310-1.634)
GSM50	336-340	1525-2000	(1.994-2.615)

GSH available in 4 and 5 tine version. GSM only available in 5 tine version.



Recycling and Demolition Grabs

	Model	Capacity m ³	(yd ³)	Weight Kg	(lb)
G315B	320-323	0.800	(1.05)	2030	(4475)
G320B	320-329	0.900	(1.18)	2250	(4960)
G325B	325-336	0.900	(1.18)	2370	(5225)
G330B	329-340	1.000	(1.30)	2950	(6504)

G310B and G315B are also available with fixed upper head (fixed mounting bracket) for less weight and lower build-up height.

Multi-Processors



Jaw Set		Model	Force at Primary Blade kN	(Sh Ton)	Jaw Opening mm	(in)
Concrete Crusher	MP15	320-329	2100	(236)	710	(28)
	MP20	324-336	3000	(337)	820	(32)
	MP30	336	4100	(460)	975	(38)
Crusher	MP15	320-329	2200	(247)	670	(26)
	MP20	234-329	2900	(326)	850	(34)
	MP30	336	3800	(427)	1050	(41)
Primary Pulverizer	MP15	320-329	2100	(236)	700	(28)
	MP20	324-329	2750	(309)	800	(32)
	MP30	336	3950	(444)	960	(38)
Secondary Pulverizer	MP15	320-329	2200	(247)	730	(29)
	MP20	324-329	3000	(337)	890	(35)
	MP30	336	4800	(539)	1100	(43)
Shear	MP15	320-329	2100	(236)	390	(15)
	MP20	324-329	2900	(326)	420	(17)
	MP30	336	3750	(421)	470	(19)
Tank Shear	MP20	324-329	2200	(247)	400	(17)
	MP30	336	4000	(449)	210	(20)

Excavators (Medium)

320-340



Excavator Rippers

	Model	Shank Length		Weight Range	
		mm	(in)	kg	(lb)
Excavator	All	1084/1290	(43-51)	419-875	(924-1929)



Secondary Pulverizers

Model	Crushing force at tip	Jaw Depth		Jaw Opening	
		t	(st)	mm	(in)
P215	320-324	119	(131)	722	(28) 838 (33)
P225	324-336	174	(192)	899	(35) 1018 (40)
P235	336	190	(209)	1103	(43) 1214 (48)



Scan here to see Secondary Pulverizers in action!



Shears

Model	Force at Throat	Jaw Opening	
		kN	(Sh Ton)
S320B	320-329	3706	(417) 409 (16)
S325B	316-336	5562	(625) 528 (21)
S340B	320-340	6818	(766) 563 (22)



Concrete Crushers

Carrier Weight (t)	Crushing force at tip	Crushing force at cutter	Jaw Depth	Jaw Opening	
					mm
P315	320-324	90	190	657	731
P325	320-336	125	295	753	855
P335	329-340	160	355	877	983



Hammers

Model	Operating Weight	Blow Rate	Tool Diameter			
			kg	(lb)	mm	(in)
H115E s	320	1170	(2579)	370-800	109	(4.31)
H120E s	320-329	1600	(3527)	350-620	119	(4.70)
H130E s	All	1910	(4211)	320-600	130	(5.0)
H140D s	324-336	2350	(5170)	350-600	140	(5.51)
H160D s	336	3150	(6946)	380-560	160	(6.30)



Scan here to see E Series Hammers in action!



Vibratory Plate Compactors

Model	Impulse Force	Cycles/min	Base Plate Width			
			kN	(lbf)	mm	(in)
CVP110	320-336	110	(24669)	2200	864	(34)