

Excavators (Large)

345-390



Buckets

	Model	Width Range mm	(in)	Capacity Range m ³	(yd ³)
General Duty	345-390	1370-2000	(539-787)	1.87-4.60	(2.44-6.01)
Heavy Duty	345-390	1500-1750	(590-689)	2.14-4.10	(2.80-5.36)
Severe Duty	345-390	1550-2240	(610-882)	2.14-5.40	(2.80-7.06)
Extreme Duty	345-390	1550-2090	(610-822)	2.61-6.00	(3.41-5.50)



Couplers

	Model	Linkage	Weight kg	Hydraulic / Mechanical
Quick Coupler	CW-55-D.6.N	TB	742	Mechanical
Quick Coupler	CW-55-H.6.N	TB	762	Hydraulic
Quick Coupler	CW-55-D.6.N	UB	830	Mechanical
Quick Coupler	CW-55-H.6.N	UB	840	Hydraulic
Quick Coupler	CW-70-H.6.N	VB	1320	Hydraulic
Quick Coupler	CW-70-H.6.N	WB	1320	Hydraulic
Quick Coupler	CW-70-H.6.N	HB	1217	Hydraulic
Quick Coupler	CW-70-H.6.N	JC	1479	Hydraulic



Hammers

	Model	Operating Weight kg (lb)	Blow Rate blows/min	Tool Diameter mm (in)
H160D s	345	3150 (6946)	380-560	160 (6.30)
H180D s	345-374	3800 (8360)	370-520	174 (6.85)



Secondary Pulverizers

	Model	Crushing force at tip t (st)	Jaw Depth mm (in)	Jaw Opening mm (in)
P235	345-349	190 (209)	1103 (43)	1214 (48)



Concrete Crushers

	Model	Crushing force at tip	at cutter	Jaw Depth mm (in)	Jaw Opening mm (in)
P335	345-349	160	355	877 (34.52)	983 (38.70)
P360	349-374	210	455	933 (36.73)	1201 (47.28)



Multi-Processors

Jaw Set	Model	Force at Primary Blade kN (Sh Ton)	Jaw Opening mm (in)
Concrete Crusher (CR)	MP30 345-349	4100 (460)	975 (38)
	MP40 349	4400 (494)	1280 (50)
Crusher (CC)	MP30 345-349	3800 (427)	1050 (41)
	MP40 349	4650 (523)	1320 (52)
Primary Pulverizer (PP)	MP30 345-349	3950 (444)	960 (38)
Secondary Pulverizer (PS)	MP30 345-349	4800 (539)	1100 (43)
	MP40 349	5500 (618)	1400 (55)
Shear (S)	MP30 345-349	3750 (421)	470 (19)
	MP40 349	4750 (326)	630 (25)
Tank Shear (TS)	MP30 345-349	4000 (449)	210 (20)



Recycling and Demolition Grabs

	Model	Capacity m ³	(yd ³)	Weight kg	(lb)
G330	345-349	1.000	(1.30)	2950	(6504)



Excavator Rippers

	Model	Shank Length mm (in)	Weight Range kg (lb)
Excavator	All	1017-1801 (40-71)	1052-2196 (2319-4841)



Shears

	Model	Force at Throat kN (Sh Ton)	Jaw Opening mm (in)
S340B	345-349	6818 (766)	563 (22)
S365C	345-349	10342 (1162)	879 (35)
S385C	349	12509 (1405)	879 (35)



Scan here for animation of Shear with Bolt-on Piercing Tip!